



دیزل مولد امید

We Light
The Darkness

ENGINE
RANGE

OFF-ROAD,
STATIONARY AND
POWER GENERATION

This document is not contractual. In a constant effort to improve the quality of its products, Volvo Penta is committed to providing the best possible products and services. For specific information on a certain engine model, please ask your dealer or visit our website www.volvopenta.com. All models are not available on all markets. The engines in the pictures may be fitted with extra optional equipment.

**VOLVO
PENTA**
www.volvopenta.com



دیزل مولد امید

واحد فروش و خدمات تهران: ۰۲۱-۴۷۶۲۶۶۶۶
کارخانه: ۰۳۶۱-۲۵۵۳۹۸۱-۳
تلفن همراه: ۰۹۱۲ ۲۵ ۰۰ ۹۱۸

13 litre series



ELECTRICAL POWER GENERATION

Power generation engines Sta gel I and II/Tier 1 and 2

Engine	50 Hz/1 500 rpm					
	Prime power			Standby power		
	kWm	kWe	kVA	kWm	kWe	kVA
TD520GE	75	69	86	83	76	94
TAD530GE	75	69	86	83	76	94
TAD531GE	88	80	100	98	89	111
TAD532GE	112	103	129	125	115	144
TAD730GE	113	104	130	124	114	143
TAD731GE	135	124	155	148	136	170
TAD732GE	161	148	185	177	163	204
TAD733GE	177	163	204	195	179	224
TAD734GE	219	202	252	241	222	277
TAD940GE	242	223	278	267	246	307
TAD941GE	281	261	327	310	288	360
TAD1341GE	275	255	319	302	281	351
TAD1342GE	303	282	352	333	310	387
TAD1343GE	325	302	378	356	331	414
TAD1344GE	354	329	411	389	362	452
TAD1345GE	388	361	451	431	401	501
TAD1640GE	392	368	460	431	405	506
TAD1641GE	430	404	505	473	445	556
TAD1642GE	503	473	591	554	521	651
TWD1643GE	536	504	630	596	560	700

5 litre series



ELECTRICAL POWER GENERATION



16 litre series

TAD 1353 GE

Turbocharged

Type of intercooling

A = Air-to-air

W = Water-to-air

Type of fuel

D = Diesel fuel

G = Gaseous Fuel

Displacement indication (litre)

Generation

Version

Type of application

G = Gen Set

V = Versatile industry application

Exhaust emission certified



7 litre series