



Lovovl range - 50 Hz (3PHASE 380/220 – 415/240V)



Genset Model	Prime Rating (PRP)		Standby Rating (ESP)		Engine Specifications				Alternator Model	Open Set Version			Canopy Version
	KVA	KWE	KVA	KWE	Engine Model	Cylinder arrangement	Cubic Capacity (litres)	Fuel Cons 100% load (l/h)		Dimensions length x Width x Height	Weight (wet) (kg)	Fuel tank Capacity (litres)	enclosure type
LSC 32.5	27.5	22	32.5	26	1003G	3 in line	2.99	6.3/6.93	PI 144 H	1920 × 750 × 1430	110	140	CO1
LSC 47.5	43.75	35	47.5	38	1003TG	3 in line	2.99	9.42/10.4	PI 144 J	1920 × 750 × 1430	110	140	CO1
LSC 50	45	36	50	40	1004G	4 in line	3.99	9.6/10.6	UCI 224 D	2100 × 750 × 1500	155	170	CO2
LSC 70	62.5	50	70	56	1004TG	4 in line	3.99	15.0/16.6	UCI 224 E	2100 × 750 × 1500	155	170	CO2
LSC 105	95	76	105	84	1006TG1A	6 in line	5.99	19.2/21.4	UCI 274 C	2330 × 850 × 1600	190	240	CO3
LSC 115	103.8	83	115	93	1006TG2A	6 in line	5.99	21.4/23.6	UCI 274 C	2330 × 850 × 1600	190	240	CO3
LSC 150	136.3	109	150	120	1006TAG	6 in line	5.99	28.4/31.1	UCI 274 E	2330 × 850 × 1600	190	240	CO4